



ISO 9001:2008
VITAL
Electrocomp






Google Us : Vital Connectors

Manufacturer of PCB Terminal Blocks, Fuse Holders, Barrier Terminals, & Switches

Screw Type (Cage-Clamp Design) Connectors


Series 254

[Model : 254/2, 254/3]



TECHNICAL SPECIFICATIONS :

Pitch	: 2.54 mm
Nominal Rating	: 6A/63V
Dielectric Strength	: >1.5 kV
Moulded Material	: PA66 - UL94 V0 or V2
Insulation Resistance	: > 1000 M Ω @ 500 Vdc
Terminal	: Tin Plated Copper Alloy
Wire Cage	: Nickel Plated Brass
Screw	: M1.6 x 0.35 mm
	: Brass Nickel Plated Suffix "P"
	: MS Trivalent Zinc Plated Suffix "C"
Wire Size	: 0.5 mm ²
Maximum Torque	: 0.10 - 0.12 Nm



ORDERING CODE

Series	Poles	Grade
--------	-------	-------

→ 254/2 P ←

Number of Poles: 2 or 3

Grade : P or C

P = Professional Grade

C = Economy Grade

Approval Data

UL : Under Testing

cUL : Under Testing

CE : 6A/63V

► The recommended PCB hole diameter is 1.30 mm unless otherwise specified for that product.



Off/Works: 830/2, GIDC Estate, Makarpura, Vadodara - 390010

Landline: 9227979806, Telephone: 9227979801

Email: sales@vitalelectrocomp.com • Web: www.vitalelectrocomp.com

Customized Color Options Available

*Subject to Minimum Order Quantity

Google Us : Vital Connectors